

LINA⁸⁵ SUSPEND



Technical description


- > White, grey, black color electrostatic powder coated aluminium extrusion housing
- > Opal PC diffuser
- > Option: Prismatic-Microprismatic diffuser
- > Option: Switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi)
- > 220-240V AC
- > -20°C ... +35°C
- > Continuous mounting options end to end



TECHNICAL DATA

Code	W	Luminous Flux (lm)	Efficiency (lm/W)	CRI	Color Temperature	Length (mm)
113LNS85.40.03	40W	4800lm	>120 lm/W	>80	3000K - 6500K	1130mm
140LNS85.50.03	50W	6000lm	>120 lm/W	>80	3000K - 6500K	1400mm
170LNS85.60.03	60W	7200lm	>120 lm/W	>80	3000K - 6500K	1700mm
200LNS85.80.03	80W	9600lm	>120 lm/W	>80	3000K - 6500K	2000mm
310LNS85.110.03	110W	13250lm	>120 lm/W	>80	3000K - 6500K	3100mm

TECHNICAL DRAWING



W: 85mm - **H:** 85mm

L: 1130mm / 1400mm / 1700mm / 2000mm / 3100mm

LIGHT BEAM

